



Distributed by:



EASY ROOF FLAT

Floor PV mounting system

Compatible with all floors: bitumen, concrete, membrane, gravel

VARIOUS
MOUNTING VERSIONS

WIDE RANGE OF
MODULES
COMPATIBILITY

ONE VERSION
FOR ALL
ORIENTATIONS:
SOUTH
EAST/ WEST

FASTENERS
INTEGRATED

PV SLOPE
ADJUSTMENT

With only few components required for the installation, **EASY ROOF FLAT** is unparally **fast** and **economical** regardless of the the floor covering to be fitted (*bitumen membrane, concrete, gravel*) and can be installed equally South or East/West.

Lightweight and **robust** for enormous stability, each chassis includes all the components required to fix the modules.

To make transportation competitive, EASY ROOF FLAT chassis can be fitted on the top of each other. EASY ROOF FLAT chassis can be stacked (*1 chassis per PV module, up to 250 kits can be attacked on one single pallet*).

Suitable for all users

PROFESSIONALS

with ground-mounted photovoltaic power plants (up to 500 kWp)







INDIVIDUALS

with ground-mounted installation for self-consumption



Features



Buildings	<ul style="list-style-type: none"> Industrial, commercial, agricultural, residential
Floors	<ul style="list-style-type: none"> Bitumen, membrane, concrete, gravel
Methods of fixing	<ul style="list-style-type: none"> Ballasting, substructure with rails, screw hanger bolts
Orientation	<ul style="list-style-type: none"> Only one version regardless of the orientation: <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>«South» orientation</p>  </div> <div style="text-align: center;"> <p>«East / West» orientation</p>  </div> </div>
PV slope and configuration	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  <p>• 10° to 14° (1 structure per module)</p> </div> <div style="text-align: center;">  <p>• 8° to 14° (inter-module configuration)</p> </div> </div>
Compatibility	<ul style="list-style-type: none"> Framed PV modules with a width up to 1170 mm⁽¹⁾
Space between 2 rows	<ul style="list-style-type: none"> No limitation
Logistics and installation	<ul style="list-style-type: none"> 250 kits can be attached on one single pallet: Low transport costs Speed of installation: Only 3 components required, Fasteners integrated in the chassis 2 keys 6 sides (5 and 6) 3 kg / sqm (PV module and ballasting excluded) <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  </div> <div style="text-align: center;">  </div> </div>
Certifications and Manufacturer's warranty	<ul style="list-style-type: none"> 10 years



CONTACT

MA PERGOLA SOLAIRE

export@mapergolasolaire.com

www.mapergolasolaire.com

Your nearest contact:

Distributed by:

